Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - Europe

Date of issue/ Date of : 10-03-2017 Date of previous issue : 24-10-2016

revision



SAFETY DATA SHEET

TEMAFLOOR P300 HARDENER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : TEMAFLOOR P300 HARDENER

Product description: Hardener.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Painting work

Only for industrial and professional use. The product is not intended for consumer use.

1.3 Details of the supplier of the safety data sheet

Manufacturer or Distributor

Tikkurila Oyj P.O. Box 53 FI-01301 VANTAA FINLAND

Telephone +358 20 191 2000

e-mail address of person : Tikkurila Oyj, responsible for this SDS : Product Safety,

e-mail: productsafety@tikkurila.com

1.4 Emergency telephone number

Telephone number : 112

(24h)

Supplier or Manufacturer

Telephone number : √ikkurila Oyj

+358 20 191 2000 (GMT +2) Mon-Fri 8-16

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

2.2 Label elements

Hazard pictograms





Signal word : Danger

Hazard statements : H302 - Harmful if swallowed.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Version : 3

Date of issue/Date of revision 10.03.2017 Date of previous issue 24.10.2016. TEMAFLOOR P300 HARDENER

General : Not applicable.

Prevention: P261 - Avoid breathing vapor.

P280 - Wear protective gloves/clothing and eye/face protection. P284 - In case of inadequate ventilation wear respiratory protection.

P273 - Avoid release to the environment.

Response : P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water or shower.

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P310 - Immediately call a POISON CENTER or physician.

Storage : Not applicable.

Disposal : Not applicable.

Hazardous ingredients : isophorone diamine benzyl alcohol

benzyl alcohol cycloaliphatic amine

2,4,6-tris(dimethylaminomethyl)phenol

Supplemental label

elements

: Not applicable.

2.3 Other hazards

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification Regulation (EC) No. 1272/2008 [CLP]	Notes	
isophorone diamine	REACH #: 01-2119514687-32 EC: 220-666-8 CAS: 2855-13-2 Index: 612-067-00-9	≥25 - ≤50	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412	-	
benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6	≥25 - ≤50	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319	-	
cycloaliphatic amine	REACH #: 01-2119965165-33 EC: 500-101-4 CAS: 38294-64-3	≥10 - ≤25	Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412	-	
2,4,6-tris(dimethylaminomethyl) phenol	REACH #: 01-2119560597-27 EC: 202-013-9 CAS: 90-72-2	≤5	Acute Tox. 4, H302 Skin Corr. 1C, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412	-	
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Notes, if applicable, refer to Notes given in Annex VI of 1272/2008/EC.

Version : 3 2/9

Date of issue/Date of revision 24.10.2016. TEMAFLOOR P300 HARDENER 10.03.2017 Date of previous issue

SECTION 4: First aid measures

4.1 Description of first aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Show this

safety data sheet or label to the doctor if possible.

: Check for and remove any contact lenses. Immediately flush eyes with plenty of Eve contact

lukewarm water, keeping eyelids open. Continue to rinse for at least 20 minutes. Get medical attention immediately. Continue rinsing until medical attention can be

obtained.

Inhalation Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel. Get medical attention.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners. In case

of chemical burns, get medical attention as soon as possible.

Ingestion : If accidentally swallowed rinse the mouth with plenty of water (only if the person is

conscious) and obtain immediate medical attention. Remove to fresh air and keep

at rest in a position comfortable for breathing. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire. Recommended:

Alcohol resistant foam, CO₂, powders or water spray/mist.

Unsuitable extinguishing

media

: Do not use a direct water jet that could spread the fire.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : This product is not classified as flammable. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous combustion

products

: When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Use water spray to keep fire-exposed containers cool. This material is hazardous to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Do not breathe vapor or mist. Do not get in eyes or on skin. Put on appropriate personal protective equipment (see Section 8).

6.2 Environmental precautions

: Hazardous to aquatic environment. Do not allow to enter drains, water courses or soil.

Version : 3 3/9

6.3 Methods and materials for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid breathing vapor. Avoid inhalation of dust from sanding. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. See Section 8 for information on appropriate personal protective equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored. Wash hands before breaks and immediately after handling the product. Avoid release to the environment.

7.2 Conditions for safe storage, including any incompatibilities

: Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Recommended storage temperature is +5°C ...+25°C. Store in accordance with local regulations.

7.3 Specific end use(s) : None.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

procedures

Recommended monitoring : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn (see Personal protection for both components). Provide a readily-accessible eyewash facility. Comply with the health and safety at work laws.

Individual protection measures

Eye/face protection

: Wear eye/face protection (EN166).

Hand protection

: Always wear approved protective gloves against chemicals. Gloves should be replaced regularly and if there is any sign of damage to the glove material. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Recommended glove material (EN374):

< 1 hour (breakthrough time): nitrile rubber, butyl rubber

> 8 hours (breakthrough time): laminated foil

Not recommended: PVC or natural rubber (latex) gloves

Skin protection : Wear suitable protective clothing.

Version : 3

Date of issue/Date of revision10.03.2017Date of previous issue24.10.2016.TEMAFLOOR P300 HARDENER

Respiratory protection

: If ventilation is inadequate, use respirator that will protect against dust/mist. Wear a half mask or full face respirator with gas and vapor filter A and dust filter P2 during sanding (EN140:1998, EN405:2001). During continuous and long-term work the use of motor-driven or air-fed respirators is recommended (EN12941:1998). Be sure to use an approved/certified respirator or equivalent. Check that mask fits tightly and change filter regularly.

Environmental exposure controls

: For information regarding environmental protection measures, please refer to section 13 for waste handling, section 7 for handling and storage and section 1.2 for relevant identified uses of the substance or mixture and uses advised against.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.
Color : Clear.
Odor : Strong.

Odor threshold : Not relevant for the hazard assessment of the product.

pH : Not relevant for the hazard assessment of the product.

Melting point/freezing point Initial boiling point and

boiling range

: 15,4°C (benzyl alcohol) : 205,3°C (benzyl alcohol)

Flash point : >100 °C

Evaporation rate : 0,007 (butyl acetate = 1) (benzyl alcohol)

Flammability (solid, gas) : Not applicable. Product is a liquid.

Upper/lower flammability or

explosive limits

: Lower: 1,3% (benzyl alcohol) Upper: 13% (benzyl alcohol)

Vapor pressure : 0,023 kPa [room temperature] (benzyl alcohol)

Vapor density : 3,7 (benzyl alcohol)

Density : 1 g/cm³

Solubility(ies) : insoluble in water.

Partition coefficient: n-octanol/ : Not available.

water

Auto-ignition temperature : 436°C (benzyl alcohol)

Decomposition temperature : Not relevant for the hazard assessment of the product.

Viscosity : Not relevant for the hazard assessment of the product.

Explosive properties : No explosive ingredients present.

Oxidizing properties : No oxidizing ingredients present.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : See Section 10.5.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid extreme heat and freezing.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents strong acids strong alkalis

Version : 3 5/9

10.6 Hazardous decomposition products

: When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There is no testdata available on the product itself.

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Long term exposure causes irritation of respiratory system and mucous membranes of nose and throat. Prolonged contact can cause severe irritation or even burns.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
sophorone diamine	LD50 Oral	Rat	1030 mg/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	4,178 mg/l	4 hours
	LD50 Oral	Rat	1230 mg/kg	-
2,4,6-tris (dimethylaminomethyl) phenol	LD50 Oral	Rat	1673 mg/kg	-

Harmful if swallowed.

Irritation/Corrosion

Causes severe skin burns and eye damage.

Sensitization

May cause an allergic skin reaction.

Mutagenicity

Not classified.

Carcinogenicity

Not classified.

Reproductive toxicity

Not classified.

Teratogenicity

Not classified.

Specific target organ toxicity (single exposure)

Not classified.

Specific target organ toxicity (repeated exposure)

Not classified.

Aspiration hazard

Not classified.

SECTION 12: Ecological information

Ecological testing has not been conducted on this product.

Do not allow to enter drains, water courses or soil.

The product is classified as environmetally hazardous according to Regulation (EC) 1272/2008. Harmful to aquatic life with long lasting effects.

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
ycloaliphatic amine	Acute LC50 70,7 mg/l	Fish	96 hours

12.2 Persistence and degradability

Version : 3 6/9

Product/ingredient name	Test	Result		Dose		Inoculum
cycloaliphatic amine	OECD 301F	0 % - Not r	eadily - 28 days	-		-
Product/ingredient name	Aquatic half-life		Photolysis	•	Biodeg	radability
cycloaliphatic amine	-		-		Not rea	dily

24.10.2016.

TEMAFLOOR P300 HARDENER

10.03.2017 Date of previous issue

12.3 Bioaccumulative potential

Date of issue/Date of revision

Product/ingredient name	LogP _{ow}	Bioconcentration factor [BCF]	Potential
2,4,6-tris (dimethylaminomethyl) phenol	0,219	-	low
cycloaliphatic amine	-	5,13	low
benzyl alcohol	0,87	-	low
isophorone diamine	0,99	-	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable. vPvB : Not applicable.

12.6 Other adverse effects : Not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : Gather residues into waste containers. Liquid residue and cleaning liquids are

hazardous waste and must not be emptied into drains or sewage system, but handled in accordance with national regulations. Product residues should be left at

special companies which have permission for gathering this kind of wastes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging

Methods of disposal : Empty packaging should be recycled or disposed of in accordance with national

regulations.

Special precautions : Note! The ready for use mixture of paint and hardener generates much heat. Allow

the remainder of the mixture to harden in a safe place, e.g. in the open.

Version :3

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number	UN2289	UN2289	UN2289
14.2 UN proper shipping name	ISOPHORONEDIAMINE	ISOPHORONEDIAMINE	Isophoronediamine
14.3 Transport hazard class(es)	8	8	8
14.4 Packing group	III	III	III
14.5 Environmental hazards	No.	No.	No.
Additional information	Hazard identification number 80 Limited quantity 5 L Tunnel code (E)	Emergency schedules (EmS) F-A,S-B	Passenger and Cargo Aircraft Quantity limitation: 5 L Packaging instructions: 852 Cargo Aircraft Only Quantity limitation: 60 L Packaging instructions: 856 Limited Quantities - Passenger Aircraft Quantity limitation: 1 L Packaging instructions: Y841 Special provisions A803

user

14.6 Special precautions for: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of **MARPOL** and the IBC Code : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Other EU regulations

Europe inventory : All components are listed or exempted.

VOC Directive : This product is in scope of Directive 2004/42/CE.

15.2 Chemical Safety **Assessment**

: This product contains substances for which Chemical Safety Assessments are still required.

Version: 3 8/9

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

: ATE = Acute Toxicity Estimate

acronyms

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification

Justification

Acute Tox. 4, H302 Calculation method Skin Corr. 1B, H314 Calculation method Skin Sens. 1, H317 Calculation method Aquatic Chronic 3, H412 Calculation method

Full text of abbreviated H

statements

: H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H412 Harmful to aquatic life with long lasting effects.

Full text of classifications

[CLP/GHS]

: Acute Tox. 4, H302 ACUTE TOXICITY (oral) - Category 4
Acute Tox. 4, H312 ACUTE TOXICITY (dermal) - Category 4
Acute Tox. 4, H332 ACUTE TOXICITY (inhalation) - Category 4
Aquatic Chronic 3, H412 AQUATIC HAZARD (LONG-TERM) - Category 3

Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2

Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B Skin Corr. 1C, H314 SKIN CORROSION/IRRITATION - Category 1C

Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1

Date of issue/ Date of

revision

: 10-03-2017

Date of previous issue : 24-10-2016

Version : 3

Notice to reader

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006 (REACH). The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Version : 3 9/9