2015/830 - Europe

Date of issue/ Date of : 2/21/2022 Date of previous issue : 7/29/2020 revision



# SAFETY DATA SHEET

### **TEMAFLOOR PU FLEX**

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : TEMAFLOOR PU FLEX

**Product description**: A two-component polyurethane paint.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Painting work

### 1.3 Details of the supplier of the safety data sheet

**Manufacturer or Distributor** 

Tikkurila Oyj P.O. Box 53 FI-01301 VANTAA FINLAND

Telephone +358 20 191 2000

e-mail address of person : Tikkurila Oyj, responsible for this SDS : Product Safety,

e-mail: productsafety@tikkurila.com

#### 1.4 Emergency telephone number

Telephone number : 112

(24h)

Supplier or Manufacturer

Telephone number : Tikkurila Oyj

+358 20 191 2000 (GMT +2) Mon-Fri 8-16

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

### 2.2 Label elements

**Signal word** : No signal word.

**Hazard statements** : No hazard statements.

**Precautionary statements** 

General : Not applicable.

Prevention : Not applicable.

Response : Not applicable.

Storage : Not applicable.

Disposal : Not applicable.

**Supplemental label**: Warning! Hazardous respirable droplets may be formed when sprayed. Do not

**elements** breathe spray or mist.

Version : 3

#### 2.3 Other hazards

Eye contact

Other hazards which do not result in classification

: None known.

## **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Notes, if applicable, refer to Notes given in Annex VI of 1272/2008/EC.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General : In a

: In all cases of doubt, or when symptoms persist, seek medical attention. Show this safety data sheet or label to the doctor if possible.

salety data silect of label to the doctor if possible.

: Check for and remove any contact lenses. Immediately flush eyes with plenty of lukewarm water, keeping eyelids open. Continue to rinse for at least 15 minutes.

**Inhalation**: Remove to fresh air.

**Skin contact**: Wash skin thoroughly with soap and water or use recognized skin cleanser. Do

NOT use solvents or thinners.

**Ingestion** : If accidentally swallowed rinse the mouth with plenty of water (only if the person is

conscious). If significant amounts have been swallowed or if symptoms persist,

seek medical attention.

### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

#### 4.3 Indication of any immediate medical attention and special treatment needed

None.

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire. Recommended:

Alcohol resistant foam, CO<sub>2</sub>, powders or water spray/mist.

Unsuitable extinguishing

: Do not use a direct water jet that could spread the fire.

media

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: This product is not classified as flammable. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous combustion products

: When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Use water spray to keep fire-exposed containers cool. Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters

: Appropriate breathing apparatus may be required.

Version : 3 2/7

### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

: Refer to protective measures listed in sections 7 and 8.

**6.2 Environmental precautions** 

: Do not allow to enter drains, water courses or soil.

6.3 Methods and materials for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 13 for additional waste treatment information.

### **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

: Avoid contact with skin and eyes. Avoid breathing vapor. Avoid inhalation of dust from sanding. See Section 8 for information on appropriate personal protective equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored. Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

: Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Recommended storage temperature is +5°C ...+25°C. Store in accordance with local regulations.

7.3 Specific end use(s) : None.

### SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

**DNELs/DMELs** 

No DNELs/DMELs available.

**PNECs** 

No PNECs available.

#### 8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn (see Personal protection for both components). Comply with the health and safety at work laws.

Individual protection measures

**Eye/face protection**: Safety eyewear should be used when there is a likelihood of exposure.

Version :3 3/7

Date of issue/Date of revision 21.02.2022 Date of previous issue TEMAFLOOR PU FLEX

Hand protection : Wear protective gloves. Gloves should be replaced regularly and if there is any

> sign of damage to the glove material. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be

followed.

Recommended glove material (EN374): > 8 hours (breakthrough time): nitrile rubber

Not recommended: PVA gloves

Skin protection : Wear appropriate personal protective clothing to prevent skin contact.

: If ventilation is inadequate, use respirator that will protect against dust/mist. Wear Respiratory protection a half mask or full face respirator with gas and vapor filter A and dust filter P2

during sanding (EN140:1998, EN405:2001). During continuous and long-term work the use of motor-driven or air-fed respirators is recommended (EN12941:1998). Be sure to use an approved/certified respirator or equivalent. Check that mask fits

tightly and change filter regularly.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

**Appearance** 

**Physical state** : Liquid. Color : Coloured Odor : Strong.

: Not relevant for the hazard assessment of the product. **Odor threshold** Hq Not relevant for the hazard assessment of the product.

Melting point/freezing point Initial boiling point and

boiling range

: Not available. : Not available.

: >100 °C Flash point **Evaporation rate** : Not available.

Flammability (solid, gas) : Not applicable. Product is a liquid.

Upper/lower flammability or

explosive limits

: Not available.

: Not available. Vapor pressure Not available. Vapor density **Density** 1.4 g/cm<sup>3</sup> Solubility(ies) : Not available. Partition coefficient: n-octanol/:

Not applicable.

**Auto-ignition temperature** : Not available.

**Decomposition temperature** : Not relevant for the hazard assessment of the product. **Viscosity** Not relevant for the hazard assessment of the product.

**Explosive properties** : No explosive ingredients present. Oxidizing properties : No oxidizing ingredients present.

**Particle characteristics** 

Median particle size : Not applicable.

9.2 Other information

No additional information.

Version: 3

Date of issue/Date of revision 21.02.2022 Date of previous issue 29.07.2020. TEMAFLOOR PU FLEX

### **SECTION 10: Stability and reactivity**

**10.1 Reactivity** : See Section 10.5.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : Avoid extreme heat and freezing.

**10.5 Incompatible materials**: Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents strong acids strong alkalis

10.6 Hazardous decomposition products

: When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

### **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

There is no testdata available on the product itself.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

**Acute toxicity** 

Not classified.

Irritation/Corrosion

Not classified.

Sensitization

Not classified.

Mutagenicity

Not classified.

Carcinogenicity

Not classified.

Reproductive toxicity

Not classified.

**Teratogenicity** 

Not classified.

Specific target organ toxicity (single exposure)

Not classified.

Specific target organ toxicity (repeated exposure)

Not classified.

**Aspiration hazard** 

Not classified.

### **SECTION 12: Ecological information**

Ecological testing has not been conducted on this product.

The product is not classified as environmentally hazardous according to Regulation (EC) 1272/2008.

Do not allow to enter drains, water courses or soil.

12.1 Toxicity : No specific data.

Not available.

Version : 3 5/7

TEMAFLOOR PU FLEX Date of issue/Date of revision 21.02.2022 Date of previous issue 29.07.2020.

12.2 Persistence and

degradability

: No specific data.

12.3 Bioaccumulative

potential

: No specific data.

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

**Mobility** : Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Other adverse effects : Not available.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

**Product** 

**Methods of disposal** 

: Gather residues into waste containers. Liquid residue must not be emptied into drains or sewage system, but handled in accordance with national regulations. Product residues should be left at special companies which have permission for gathering this kind of wastes.

#### European waste catalogue (EWC)

Waste code	Waste designation		
08 01 11* 08 01 12	waste paint and varnish containing organic solvents or other hazardous substances waste paint and varnish other than those mentioned in 08 01 11		

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

**Packaging** 

Methods of disposal

: Empty packaging should be recycled or disposed of in accordance with national

regulations.

Special precautions Note! The ready for use mixture of paint and hardener generates much heat. Allow

the remainder of the mixture to harden in a safe place, e.g. in the open.

### **SECTION 14: Transport information**

This product is not regulated for carriage according to ADR/RID, IMDG, IATA.

	ADR/RID	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.

Version : 3

29.07.2020

TEMAFLOOR PU FLEX

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

### SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Other EU regulations

**Europe inventory** : At least one component is not listed.

**Persistent Organic Pollutants** 

Not listed.

15.2 Chemical Safety **Assessment** 

: This product contains substances for which Chemical Safety Assessments are still required.

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and

acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification **Justification** 

Not classified.

Full text of abbreviated H

statements

: Not applicable.

Full text of classifications

[CLP/GHS]

: Not applicable.

Date of issue/ Date of

revision

: 2/21/2022

Date of previous issue : 7/29/2020

Version

#### Notice to reader

This Safety Data Sheet is prepared in accordance with Annex II (EU) No 830/2015 to Regulation (EC) No 1907/2006 (REACH). The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Version : 3