



# SAFETY DATA SHEET

TEMALAC AB 70

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name : TEMALAC AB 70  
Product code : 610-s  
Product description : Alkyd topcoat.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Painting work

### 1.3 Details of the supplier of the safety data sheet

#### Manufacturer or Distributor


Tikkurila Oyj  
P.O. Box 53  
FI-01301 VANTAA  
FINLAND  
Telephone +358 20 191 2000

e-mail address of person responsible for this SDS : Tikkurila Oyj,  
Product Safety,  
e-mail: productsafety@tikkurila.com

### 1.4 Emergency telephone number

Telephone number : 112  
(24h)

#### Supplier or Manufacturer

Telephone number :  Tikkurila Oyj  
+358 20 191 2000 Mon-Fri 8-16

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

STOT SE 3, H336

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

### 2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 - Flammable liquid and vapor.  
H336 - May cause drowsiness or dizziness.

Precautionary statements

General : Not applicable.

<b>Prevention</b>	: P261 - Avoid breathing mist/vapors/spray. P284 - In case of inadequate ventilation wear respiratory protection. P210 - Keep away from sparks and open flames. - No smoking.
<b>Response</b>	: Not applicable.
<b>Storage</b>	: Not applicable.
<b>Disposal</b>	: Not applicable.
<b>Hazardous ingredients</b>	: hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
<b>Supplemental label elements</b>	: Contains Fatty acids, tall-oil, compds. with oleylamine, cobalt bis(2-ethylhexanoate) and ethyl methyl ketoxime. May produce an allergic reaction.  Wear protective gloves.

### 2.3 Other hazards

Other hazards which do not result in classification : None known.

## SECTION 3: Composition/information on ingredients

3.2 Mixtures		: Mixture		
Product/ingredient name	Identifiers	%	Classification Regulation (EC) No. 1272/2008 [CLP]	Notes
hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	REACH #: 01-2119463258-33 EC: 919-857-5 CAS: -	≥25 - ≤50	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066	H,P
Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene	REACH #: *) EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	<10	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304	C
aluminium powder (stabilised)	REACH #: 01-2119529243-45 EC: 231-072-3 CAS: 7429-90-5 Index: 013-002-00-1	≤5	Flam. Sol. 1, H228	T
2-ethylhexanoic acid, zirconium salt	REACH #: 01-2119979088-21 EC: 245-018-1 CAS: 22464-99-9	≤1	Repr. 2, H361d (Unborn child)	-
ethyl methyl ketoxime	REACH #: 01-2119539477-28 EC: 202-496-6 CAS: 96-29-7 Index: 616-014-00-0	≤0,3	Acute Tox. 4, H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351	-
cobalt bis(2-ethylhexanoate)	REACH #: 01-2119524678-29 EC: 205-250-6 CAS: 136-52-7	<0,25	Eye Irrit. 2, H319 Skin Sens. 1, H317 Repr. 2, H361f (Fertility) Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	-
Fatty acids, tall-oil, compds. with oleylamine	REACH #: 01-2119974148-28 EC: 288-315-1 CAS: 85711-55-3	<0,1	Eye Dam. 1, H318 Skin Sens. 1A, H317 STOT RE 2, H373  <b>See Section 16 for the full text of the H statements declared above.</b>	-

The REACH numbers of Reaction mass of m-xylene and o-xylene and p-xylene and ethylbenzene are 01-2119488216-32 and 01-2119555267-33.

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Notes, if applicable, refer to Notes given in Annex VI of 1272/2008/EC.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

<b>General</b>	: In all cases of doubt, or when symptoms persist, seek medical attention. Show this safety data sheet or label to the doctor if possible.
<b>Eye contact</b>	: Check for and remove any contact lenses. Immediately flush eyes with plenty of lukewarm water, keeping eyelids open. Continue to rinse for at least 15 minutes. Get medical attention if symptoms occur.
<b>Inhalation</b>	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention.
<b>Skin contact</b>	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
<b>Ingestion</b>	: If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Remove to fresh air and keep at rest in a position comfortable for breathing. Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness.

See Section 11 for more detailed information on health effects and symptoms.

Contains:

cobalt bis(2-ethylhexanoate)

ethyl methyl ketoxime

Fatty acids, tall-oil, compds. with oleylamine

May produce an allergic reaction.

### 4.3 Indication of any immediate medical attention and special treatment needed

None.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

<b>Suitable extinguishing media</b>	: Use an extinguishing agent suitable for the surrounding fire. Recommended: Alcohol resistant foam, CO <sub>2</sub> , powders or water spray/mist.
<b>Unsuitable extinguishing media</b>	: Do not use a direct water jet that could spread the fire.

### 5.2 Special hazards arising from the substance or mixture

<b>Hazards from the substance or mixture</b>	: Flammable liquid and vapor. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.
<b>Hazardous combustion products</b>	: When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

### 5.3 Advice for firefighters

<b>Special protective actions for fire-fighters</b>	: Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. Do not release runoff from fire to drains or watercourses.
<b>Special protective equipment for fire-fighters</b>	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures** : Shut off all ignition sources. No flares, smoking or flames in hazard area. Provide adequate ventilation. Avoid breathing vapor or mist. Avoid direct skin contact with product. See Section 8 for information on appropriate personal protective equipment.
- 6.2 Environmental precautions** : Do not allow to enter drains, water courses or soil.
- 6.3 Methods and materials for containment and cleaning up** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with a detergent. Avoid using solvents.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

- 7.1 Precautions for safe handling** : Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. Isolate from sources of heat, sparks and open flame. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. No sparking tools should be used.  
Skin contact with the product and exposure to spray mist and vapor should be avoided. Avoid inhalation of dust from sanding. Wear appropriate respirator when ventilation is inadequate. See Section 8 for information on appropriate personal protective equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored. Wash hands before breaks and immediately after handling the product.  
**Risk of self-ignition!** Materials such as cleaning rags and paper wipes, sanding dust and overspray containing the product, may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be placed in a metal container filled with water and sealed or dried preferably outdoors or incinerated immediately. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.
- 7.2 Conditions for safe storage, including any incompatibilities** : Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). No smoking. Store and use away from heat, sparks, open flame or any other ignition source. Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Recommended storage temperature is +5°C ...+25°C. Store in accordance with local regulations.
- 7.3 Specific end use(s)** : None.

## SECTION 8: Exposure controls/personal protection

8.1 Control parameters	
Occupational exposure limits	
Product/ingredient name	Exposure limit values

Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene

**EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values**

TWA: 50 ppm 8 hours.  
TWA: 221 mg/m<sup>3</sup> 8 hours.  
STEL: 100 ppm 15 minutes.  
STEL: 442 mg/m<sup>3</sup> 15 minutes.

Additional information

### Ethylbenzene

**EU OEL (Europe, 12/2009). Absorbed through skin.**

TWA: 100 ppm 8 hours.  
TWA: 442 mg/m<sup>3</sup> 8 hours.  
STEL: 200 ppm 15 minutes.  
STEL: 884 mg/m<sup>3</sup> 15 minutes.

Please check your local legislation for national OEL value for ethylbenzene.

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

### DNELs/DMELs

No DNELs/DMELs available.

### PNECs

No PNECs available.

## 8.2 Exposure controls

### Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof ventilation equipment. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn (see Personal protection). Comply with the health and safety at work laws.

### Individual protection measures

- Eye/face protection** : Use safety eyewear designed to protect against splash of liquids (EN166).
- Hand protection** : Wear protective gloves. Gloves should be replaced regularly and if there is any sign of damage to the glove material. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.  
Recommended glove material (EN374):  
> 8 hours (breakthrough time): nitrile rubber, laminated foil
- Skin protection** : Wear suitable protective clothing. This product is classified as flammable. If necessary, personnel should wear antistatic clothing made of natural fibers or of high-temperature-resistant synthetic fibers.
- Respiratory protection** : If ventilation is inadequate, use respirator that will protect against organic vapor and dust/mist. During spray-application use respirators with combination filter A/P3 (EN405:2001). Wear a half mask or full face respirator with gas and vapor filter A and dust filter P2 during sanding (EN140:1998, EN405:2001). During continuous and long-term work the use of motor-driven or air-fed respirators is recommended (EN12941:1998). Be sure to use an approved/certified respirator or equivalent. Check that mask fits tightly and change filter regularly.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Color** : Coloured
- Odor** : Strong.
- Odor threshold** : Not relevant for the hazard assessment of the product.
- pH** : Not relevant for the hazard assessment of the product.
- Melting point/freezing point** : <-15°C (hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

<b>Initial boiling point and boiling range</b>	: 150 to 200°C (hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
<b>Flash point</b>	: 36 °C (hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
<b>Evaporation rate</b>	: Not relevant due the nature of the product.
<b>Flammability (solid, gas)</b>	: Not applicable. Product is a liquid.
<b>Upper/lower flammability or explosive limits</b>	: Lower: 0,6% (hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics) Upper: 7% (hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
<b>Vapor pressure</b>	: 0,3 kPa [room temperature] (hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
<b>Vapor density</b>	: >3 (hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
<b>Density</b>	: 1,1 to 1,2 g/cm <sup>3</sup>
<b>Solubility(ies)</b>	: Insoluble in water.
<b>Partition coefficient: n-octanol/ water</b>	: Not available.
<b>Auto-ignition temperature</b>	: 250°C (hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
<b>Decomposition temperature</b>	: Not relevant for the hazard assessment of the product.
<b>Viscosity</b>	: Kinematic (40°C): >20,5 mm <sup>2</sup> /s >30 s [ISO 3mm cup] >60 s [ISO 6mm cup]
<b>Explosive properties</b>	: No explosive ingredients present.
<b>Oxidizing properties</b>	: No oxidizing ingredients present.

## 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

<b>10.1 Reactivity</b>	: See Section 10.5.
<b>10.2 Chemical stability</b>	: Stable under recommended storage and handling conditions (see Section 7).
<b>10.3 Possibility of hazardous reactions</b>	: May present an explosion hazard when material is suspended in air in confined areas or equipment and subjected to spark, heat or flame.
<b>10.4 Conditions to avoid</b>	: Avoid extreme heat and freezing. Avoid all possible sources of ignition (spark or flame).
<b>10.5 Incompatible materials</b>	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents strong acids strong alkalis
<b>10.6 Hazardous decomposition products</b>	: When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

There is no testdata available on the product itself.

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting.

**Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
☑ Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene	LC50 Inhalation Vapor	Rat	22 mg/l	4 hours
	LD50 Dermal	Rabbit	1700 mg/kg	-
	LD50 Oral	Rat	4300 mg/kg	-

Not classified.

**Irritation/Corrosion**

Not classified.

**Sensitization**

☑ Contains small amounts of sensitizing substances:

cobalt bis(2-ethylhexanoate)

ethyl methyl ketoxime

Fatty acids, tall-oil, compds. with oleylamine

**Mutagenicity**

Not classified.

**Carcinogenicity**

Not classified.

**Reproductive toxicity**

Not classified.

**Teratogenicity**

Not classified.

**Specific target organ toxicity (single exposure)**

May cause drowsiness or dizziness.

**Specific target organ toxicity (repeated exposure)**

Not classified.

**Aspiration hazard**

Not classified.

## SECTION 12: Ecological information

Ecological testing has not been conducted on this product.

Do not allow to enter drains, water courses or soil.

The product is not classified as environmentally hazardous according to Regulation (EC) 1272/2008.

**12.1 Toxicity**

Product/ingredient name	Result	Species	Exposure
☑ cobalt bis(2-ethylhexanoate)	IC50 0,528 mg/l	Algae	72 hours

**12.2 Persistence and degradability**

: No specific data.

**12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	Bioconcentration factor [BCF]	Potential
cobalt bis(2-ethylhexanoate)	-	15600	high
ethyl methyl ketoxime	0,63	2.5 to 5.8	low
2-ethylhexanoic acid, zirconium salt	-	2,96	low
Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene	3,12	8.1 to 25.9	low

#### 12.4 Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Mobility : Not available.

#### 12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

12.6 Other adverse effects : Not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : Gather residues into waste containers. Liquid residue and cleaning liquids are hazardous waste and must not be emptied into drains or sewage system, but handled in accordance with national regulations. Product residues should be left at special companies which have permission for gathering this kind of wastes.

#### European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

#### Packaging

**Methods of disposal** : Empty packaging should be recycled or disposed of in accordance with national regulations.

**Special precautions** : **Risk of self-ignition!** Materials such as cleaning rags and paper wipes, sanding dust and overspray containing the product, may spontaneously self-ignite some hours later. To avoid the risks of fires, waste like this should be placed in a metal container filled with water and sealed before disposal, or dried preferably outdoors or incinerated immediately.

## SECTION 14: Transport information

	ADR/RID	IMDG	IATA
<b>14.1 UN number</b>	UN1263	UN1263	UN1263
<b>14.2 UN proper shipping name</b>	PAINT	PAINT	PAINT
<b>14.3 Transport hazard class(es)</b>	3	3	3



<b>14.4 Packing group</b>	III	III	III
<b>14.5 Environmental hazards</b>	No.	No.	No.
<b>Additional information</b>	<p><b>Special provisions</b> 640 (E)</p> <p><b>Viscous substance exemption</b> This class 3 material is not subject to regulation in packagings up to 450 L. Exempted according to 2.2.3.1.5 (Viscous substance exemption)</p> <p><b>Tunnel code</b> (D/E)</p>	<p><b>Emergency schedules (EmS)</b> F-E,S-E</p> <p><b>Viscous substance exemption</b> This class 3 material is not subject to regulation in packagings up to 30 L. Exempted according to 2.3.2.5 (Viscous substance exemption)</p>	-

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Other EU regulations

Europe inventory : Not determined.

Industrial emissions : Listed

(integrated pollution prevention and control) -  
Air

Product/ingredient name	Carcinogenic effects	Mutagenic effects	Developmental effects	Fertility effects
2-ethylhexanoic acid, zirconium salt	-	-	Repr. 2, H361d (Unborn child)	-
ethyl methyl ketoxime	Carc. 2, H351	-	-	-
cobalt bis (2-ethylhexanoate)	-	-	-	Repr. 2, H361f (Fertility)

VOC Directive : This product is in scope of Directive 2004/42/CE.

**15.2 Chemical Safety Assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

: ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number  
 vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

	Classification	Justification
Flam. Liq. 3, H226 STOT SE 3, H336		On basis of test data Calculation method
<b>Full text of abbreviated H statements</b>	: <span style="color: blue;">■</span> H226 Flammable liquid and vapor. H228 Flammable solid. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361d Suspected of damaging the unborn child. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects.	
<b>Full text of classifications [CLP/GHS]</b>	: <span style="color: blue;">■</span> Acute Tox. 4, H312 ACUTE TOXICITY (dermal) - Category 4 Acute Tox. 4, H332 ACUTE TOXICITY (inhalation) - Category 4 Aquatic Acute 1, H400 AQUATIC HAZARD (ACUTE) - Category 1 Aquatic Chronic 1, H410 AQUATIC HAZARD (LONG-TERM) - Category 1 Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1 Carc. 2, H351 CARCINOGENICITY - Category 2 EUH066 Repeated exposure may cause skin dryness or cracking. Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3 Flam. Sol. 1, H228 FLAMMABLE SOLIDS - Category 1 Repr. 2, H361d TOXIC TO REPRODUCTION (Unborn child) - Category 2 Repr. 2, H361f TOXIC TO REPRODUCTION (Fertility) - Category 2 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1 Skin Sens. 1A, H317 SKIN SENSITIZATION - Category 1A STOT RE 2, H373 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 STOT SE 3, H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 STOT SE 3, H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	
<b>Date of issue/ Date of revision</b>	: 14-10-2016	
<b>Date of previous issue</b>	: 24-03-2015	
<b>Version</b>	: 1.02	

### Notice to reader

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006 (REACH). The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.