

TIKKURILA UNIKKOÖLJY



POPPYSEED OIL FOR WOODEN CUTTING BOARDS, DISHES AND KITCHEN UTENSILS.

DESCRIPTION A cold-pressed, 100% drying vegetable oil for the treatment of wood surfaces.

RECOMMENDED USES Untreated wood surfaces, such as cutting boards, wooden dishes and utensils. Suitable for the

treatment of toys and wooden surfaces that come into contact with food.

PRODUCT FEATURES Unikkoöljy protects wood surfaces from moisture and dirt, and the treated surfaces are easy to

keep clean.



UNIKKOÖLJY

TECHNICAL DATA

Colour Shades Colorless, deepens the color of the treated wood.

Coverage 10–25 m2/l, depending on the porosity of the surface.

Can sizes 0.375 l

Application method Brush or application with a clean cloth.

Drying time (23°C and 50% relative air humidity)

The oil soaks into the wood. Wipe off any surplus oil. The surface will withstand use

in one to three days of treatment.

Density (kg/l) 0,9 kg/l, ISO 2811.

Volume solids (%) 100

Weight solids (%) 0,9 kg/l, ISO 2811

Storage Unaffected by cold storage or transportation. The product withstands cold storage

and transportation.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



UNIKKOÖLJY

APPLICATION INSTRUCTIONS

Application conditions

The surface to be treated must be dry. The minimum ambient temperature for use of the product is +10 °C and the relative humidity of air below 80%.

Surface preparation

Clean the wood surfaces carefully and let them dry. Washing-up liquid can be used to clean the surfaces. Very dirty or discolored surfaces can be scraped or sanded before treatment.

Application

Apply Unikkoöljy Poppy Oil with a brush or clean cloth, and let the product soak into the wood. Wipe any surplus oil off with a clean cloth.

Cleaning of tools

Wash the tools first with warm water and soap, and clean any remnants with Tikkurila Tool Cleaner.

Maintenance instructions

Wipe the surface lightly with a damp sponge or cloth and neutral (pH 6– 8) washing-up liquid. Do not leave the surface wet. If necessary, apply a new coat of poppy oil. Retreat worn surfaces with Unikkoöljy Poppy Oil. A surface regularly treated with poppy oil is water-resistant, easy to keep clean, and hardwearing.

Environmental protection and waste disposal

Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations. Note! Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials can create fire some hours later and should be soked in water and placed in a closed metal container before disposal.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.