

TIKKURILA
VALTTI AKVABASE



- DESCRIPTION** Waterborne priming oil for wood.
- RECOMMENDED USES** All wooden structures to be treated with wood stains or paints (except surfaces to be treated with wood oils and barn-red paints) and exterior woodwork. Can be used on wood components above grounds. Not for use on wood in direct soil contact or in marine environment.
- PRODUCT FEATURES** For protection and priming of timber and wooden structures before surface treatment. Suitable for sawn and planed timber, logs, thermally treated and impregnated wood in exterior use. Not to be used in interior surfaces. Not to be used on wood in direct contact with foodstuffs or animal nutrition. Use the product only as wood preservative as described in product data sheet and label.
- Use wood preservatives safely. Always read the label and product information before use.
- Finishing coats are recommended to be applied as soon as possible, because colourless priming oil does not protect the wood surface from the adverse effects of sunlight.



VALTTI AKVABASE

TECHNICAL DATA

Coverage	0.18-0.22 l/m ²
Can sizes	2.7 l, 9 l
Drying time (23°C and 50% relative air humidity)	The surface is touch-dry after approx. 1/2 hour and recoatable after 24 hours.
Volume solids (%)	12
Storage	Protect from frost. Protect from frost

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



VALTTI AKVABASE

APPLICATION INSTRUCTIONS

Application conditions

The surface to be treated must be dry, the temperature of the air at least +5°C during treatment and drying, and the relative humidity of the air below 80 %.

Surface preparation

Remove dirt, mould and any loose material. Wash down surfaces affected by mould with Mould Removal (Homeenpoisto) or Tehopesu (Power Clean) solution according to directions of use. Protect other surfaces and plants from splashes of Valtti Akvabase.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.