



TIKKURILA

## VALTTI TERRACE OIL

WEATHER-RESISTANT OIL FOR TERRACES AND GARDEN FURNITURE.

**DESCRIPTION** Oil containing wax for protection and treatment of outdoor wooden surfaces.

**RECOMMENDED USES** For the treatment of garden furniture, stairs and terraces.

**PRODUCT FEATURES** For the outdoor protection and treatment of new or previously treated with oil wooden surfaces (terraces, stairs, garden furniture, berths, etc.), impregnated (under pressure) and heat-treated wood, surfaces of solid or precious wood. Effectively protects against moisture, mold, fungi and reduces cracking of the wooden surface. Can be used outdoor without additional tinting.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



TIKKURILA

## VALTTI TERRACE OIL

### TECHNICAL DATA

<b>Base paints</b>	EC BASE
<b>Colour Shades</b>	Colorless (Base EC). Tinted on the catalog Tikkurila «Valtti». To avoid differences in shade, use one batch. The final color of the coating depends on the breed and the original wood color, as well as the layers number.
<b>Gloss</b>	NA
<b>Coverage</b>	5-7 m <sup>2</sup> /l, depending on the surface absorbability.
<b>Can sizes</b>	EC BASE: 0.9 l, 2.7 l, 9 l FACTORY READYMADE SHADE: 0.9 l, 2.7 l, 9 l
<b>Thinner</b>	White Spirit 1050.
<b>Application method</b>	Brush, sponge or applicator Tikkurila.
<b>Drying time (23°C and 50% relative air humidity)</b>	Recoatable after 12 hours. Full drying after 24 hours. Attention! In case of low temperatures and high air relative humidity, the drying time may be increased.
<b>Density (kg/l)</b>	0,80 - 0,86 kg/l
<b>Volume solids (%)</b>	30-60%.
<b>Storage</b>	In tightly closed package, protecting from moisture, heat and direct sunlight. Can withstand storage at low temperatures. In case of storage at subzero temperatures before use the paint should be hold at (+20±2)°C for 24 hours and carefully stirred. Shelf life - 60 months from the production date in unopened original packaging.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



# VALTTI TERRACE OIL

## APPLICATION INSTRUCTIONS

### Application conditions

The treated surface should be dry and clean. During application and drying of the product, the temperature must be above +5°C and relative air humidity should be lower than 80%. Painting work is best done on a windless cloudy day at a temperature from +10 to +20°C.

Attention! In case of low temperatures and high air relative humidity, the drying time may be increased.

### Surface preparation

Unpainted surfaces:

Clean the surface from dirt, dust and other impurities. Wash contaminated and moldy areas with Tikkurila «Homeenpoisto», observing the instructions for use, and rinse carefully with water.

Previously painted surfaces:

Remove foreign impurities from previously oil treated surfaces with scraper and/or wire brush, clean and, if necessary, wash with Tikkurila «Homeenpoisto». If the surface remains an explicit film, it must be completely removed.

### Top coating

Stir oil before and during use. Apply on the primed surface in 1-2 layers with a sponge or a special applicator for applying oils and lacquers in the direction of wood fibers smoothly and continuously along the entire board length or on several boards at the same time, to avoid the formation of visible joints. After 20-30 minutes after application, remove the non-absorbed oil from the surface with a rag.

### Cleaning of tools

Clean tools with Tikkurila «White Spirit 1050».

### Maintenance instructions

Handle the treated surface with care as the product reaches its final wear-resistant in about one week under normal conditions. The surface can be cleaned with a soft brush or a damp cloth two days after treatment. After one month from painting, a dirty surface can be cleaned with cleaning solution. After washing, rinse with water and let dry.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.