



TIKKURILA

VENTTI PUUÖLJY RUSKEA

WOOD OIL FOR EXTERIOR USE / BROWN

DESCRIPTION

Linseed oil based wood oil for exterior use. Protects wood against moisture and dirt and decreases cracking of wood surfaces.

RECOMMENDED USES

Garden furniture, terraces, stairs, fences, railings, piers, flower planters and doors.

PRODUCT FEATURES

Suitable for oiling exterior wood surfaces. Suitable for impregnated wood (pressure-treated wood), hardwood, thermally modified wood and untreated wood.



VENTTI PUUÖLJY RUSKEA

TECHNICAL DATA

Colour Shades	Brown
Coverage	Approx. 5 m ² /l, depending on the porosity of the wood surface.
Can sizes	0.9 l, 2.7 l
Thinner	White spirit
Application method	Application with brush or sponge.
Drying time (23°C and 50% relative air humidity)	Touch-dry after approx. 4 hours. The porosity of the substrate and the amount of oil used affect the drying time. The next treatment can be carried out after the surface has dried.
Density (kg/l)	0.8 kg/l (ISO 2811)
Volume solids (%)	21
Storage	Unaffected by cold storage or transportation. Badly closed or short cans endure badly long-time storage.

VENTTI PUUÖLJY RUSKEA

APPLICATION INSTRUCTIONS

Application conditions

The surface to be treated must be dry, the temperature of the air at least +5 °C and the relative humidity of the air below 80 % during treatment and drying.

Surface preparation

New impregnated surfaces must be allowed to dry for six months before treatment. Remove dirt, dust and loose material from the wood surface. Wash old and darkened wood surfaces with Homeenpoisto mold removal or Terassi- ja Kalustepesu power clean according to instructions.

Stir Ventti Puuöljy Ruskea well before use and occasionally during use. Spread the wood oil with a brush or a sponge, pressing the tool down tightly so that all the oil is absorbed into the wood. Wipe off any excess oil. Apply evenly and continuously along the length of a board.

Cleaning of tools

Clean tools with White Spirit 1050 or Tikkurila Pensselipesu (Tool Cleaner).

Maintenance instructions

Handle the painted surface with care, as the product achieves its final hardness and durability in about 1 week under normal conditions. The surface can be cleaned lightly after about 2 days after treatment using a soft brush, a damp cleaning cloth or a mop. A dirty surface can be cleaned with Pihan Huoltipesu (mix 1 part of Pihan Huoltipesu with 10 parts of water).

Clean stains and very dirty surfaces with a stronger solution of Huoltipesu and water (1:1). After washing, rinse the surfaces and allow to dry.

Environmental and waste disposal

Avoid spillage into drains, water systems and soil. Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations. Note! Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials can create fire some hours later and should be soaked in water and placed in a closed metal container before disposal.

HEALTH AND SAFETY LABELLING according to Regulation (EC) No. 1272/2008

Contains: hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics, 2-octyl-2H-isothiazol-3-one (OIT). **DANGER.** Flammable liquid and vapor. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from sparks and open flames. - No smoking. Avoid breathing vapor. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves. **IF SWALLOWED:** Immediately call a POISON CENTER or physician. **IF ON SKIN:** Wash with plenty of soap and water. Do NOT induce vomiting.



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.